

AD-A101 022

DAVID W TAYLOR NAVAL SHIP RESEARCH AND DEVELOPMENT CE--ETC F/6 20/4
EFFECT OF BOW-DOWN TRIM ON THE RESISTANCE CHARACTERISTICS OF TH--ETC (11)
JUN 81 W 6 DAY: D 5 JENKINS
DTNSRDC/SPD-0544-16

UNCLASSIFIED

ML

1 OF 1
54 DDC

END
DATE
FILMED
7 81
DTIC

LEVEL II

P.S.

12

AD A101022

DTNSRDC/SPD-0544-16

DAVID W. TAYLOR NAVAL SHIP
RESEARCH AND DEVELOPMENT CENTER

Bethesda, Maryland 20084



EFFECT OF BOW-DOWN TRIM ON THE RESISTANCE CHARACTERISTICS
OF THE AO 177 HULL REPRESENTED BY MODEL 5326

by

William G. Day, Jr. and Douglas S. Jenkins

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED

SHIP PERFORMANCE DEPARTMENT REPORT

DTIC
ELECT
JUL 7 1981

JUNE 1981


DTNSRDC/SPD-0544-16

DTIC FILE COPY

EFFECT OF BOW-DOWN TRIM ON THE RESISTANCE CHARACTERISTICS OF THE
AO 177 HULL REPRESENTED BY MODEL 5326

81 7 06 146

MAJOR DTNSRDC ORGANIZATIONAL COMPONENTS



UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER 14 DTNSRDC/SPD-0544-16 ✓	2. GOVT ACCESSION NO. AD-A107 011	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) EFFECT OF BOW-DOWN TRIM ON THE RESISTANCE CHARACTERISTICS OF THE AO 177 HULL REPRESENTED BY MODEL 5326		5. TYPE OF REPORT & PERIOD COVERED 9 Final rept's
7. AUTHOR(s) 10 William G./Day, Jr. and Douglas S./Jenkins		6. PERFORMING ORG. REPORT NUMBER DTNSRDC/SPD-0544-16
9. PERFORMING ORGANIZATION NAME AND ADDRESS DAVID TAYLOR NAVAL SHIP R&D CENTER SHIP PERFORMANCE DEPT. BETHESDA, MD. 20084		8. CONTRACT OR GRANT NUMBER(s)
11. CONTROLLING OFFICE NAME AND ADDRESS NAVAL SEA SYSTEMS COMMAND (NAVSEA 3213) WASHINGTON, D.C. 20362		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS NAVSEA Work Request WROH301 DTNSRDC Work Unit 1524-714
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		12. REPORT DATE 11 JUNE 1981
		13. NUMBER OF PAGES 10 + iii
		15. SECURITY CLASS. (of this report) UNCLASSIFIED
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE N/A
16. DISTRIBUTION STATEMENT (of this Report) APPROVED FOR PUBLIC RELEASE: DISTRIBUTION UNLIMITED		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) AO 177 Resistance Trim by the bow Model 5326		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) Experiments were performed with a 1:25.682-scale model of the AO 177 to determine the effect of bow-down trim on the resistance of the hull. The three full-scale trim conditions represented were 1.5-foot (0.46 m) trim by the stern, 1.0-foot (0.3 m) trim by the bow, and 3.5-foot (1.07 m) trim by the bow. The results indicate a small increase in resistance at the 21.5-knot design speed with increasing trim by the bow. 7		

DD FORM 1473

EDITION OF 1 NOV 65 IS OBSOLETE
54N 0102-LF-014-5601

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

Accession For	
NTIS GRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By	
Distribution/	
Availability Codes	
Avail and/or	
Dist	

TABLE OF CONTENTS

	Page
LIST OF FIGURES.....	iii
LIST OF TABLES.....	iii
ABSTRACT.....	1
ADMINISTRATIVE INFORMATION.....	1
INTRODUCTION.....	1
DESCRIPTION OF MODEL AND EXPERIMENTS.....	2
PRESENTATION AND DISCUSSION OF RESULTS.....	2
REFERENCES.....	4

LIST OF FIGURES

	Page
1 - Effective Power Predictions for the AO 177 Hull Represented by Model 5326 at Three Trim Conditions.....	5
2 - Effective Power Requirement for AO 177 at 21.5 Knots in Various Trim Conditions.....	6

LIST OF TABLES

	Page
1 - Effective Power Predictions for AO 177 Represented by Model 5326 Design Displacement, Trimmed 1.5 ft (0.46 m) by the Stern.....	7
2 - Effective Power Predictions for AO 177 Represented by Model 5326 Design Displacement, Trimmed 3.5 ft (1.07 m) by the Bow.....	8
3 - Effective Power Predictions for AO 177 Represented by Model 5326 Design Displacement, Trimmed 1.0 ft (0.31 m) by the Bow.....	9
4 - Comparison of Effective Power Predictions for AO 177 Represented by Model 5326, Design Displacement, Fully Appended, at Three Trim Conditions.....	10

ABSTRACT

Experiments were performed with a 1:25.682-scale model of the AO 177 to determine the effect of bow-down trim on the resistance of the hull. The three full-scale trim conditions represented were 1.5-foot (0.46 m) trim by the stern, 1.0-foot (0.3 m) trim by the bow, and 3.5-foot (1.07 m) trim by the bow. The results indicate a small increase in resistance at the 21.5-knot design speed with increasing trim by the bow.

ADMINISTRATIVE INFORMATION

The work reported herein was performed for the Naval Sea Systems Command (NAVSEA) under funding provided in Work Request Number N000248OWROH301 dated February 1980. The David W. Taylor Naval Ship R&D Center (DTNSRDC) Work Unit Number was 1-1524-714.

INTRODUCTION

The contract design of the AO 177 Auxiliary Oiler represented by DTNSRDC Model 5326 was designed to have an at-rest trim of 1.5 feet (0.46 m) by the stern. The design displacement is 27,390 tons (27 820 metric tons), at a mean draft of 22.5 feet (6.9 m). When the ship was launched, it assumed an at-rest trim of approximately 3.5 feet (1.1 m) by the bow. The Naval Sea Systems Command (NAVSEA 3213) initiated a model test program in the Ship Performance Department at DTNSRDC to determine the effects of such a change in trim on both the effective power requirements and the maneuvering characteristics of the AO 177 hull. The Design Evaluation Branch (Code 1524) was tasked to perform model resistance experiments at 3 trim conditions to determine changes in drag due to the trim. The Surface Ship Dynamics Branch (Code 1568) was tasked to perform turning and maneuvering experiments to determine the effects of bow-down trim on maneuvering characteristics of AO 177.

This report presents a brief description of the model and experimental conditions for the resistance experiments. The results showing drag increase with bow-down trim are presented. The results of the turning and maneuvering experiments will be presented in a separate report.

DESCRIPTION OF MODEL AND EXPERIMENTS

DTNSRDC Model 5326-1 represents the AO 177 to a scale ratio of 25.682. For the resistance experiments reported herein the model was fitted with rudder, bilge keels and the final design bulbous bow configuration. Additional details of model configuration are presented in Reference (1).

The model was ballasted to the design displacement representing 27,390 tons (27 820 metric tons) and trimmed to represent 3 trim conditions: 1.5 feet (0.46 m) trim by the stern, 1.0 feet (0.3 m) trim by the bow and 3.5 feet (1.1 m) trim by the bow. Resistance experiments were performed on towing Carriage 1 in the deep water basin of DTNSRDC, using standard equipment and procedures.

PRESENTATION AND DISCUSSION OF RESULTS

The results of the resistance experiments are presented in Tables 1 through 3 and Figure 1. Effective power predictions have been made using the 1957 ITTC Ship-Model Correlation Line and a correlation allowance of 0.0005. Full scale effective power predictions are for the ship operating in smooth, deep salt water at 15° Celsius. Still-air drag and service margin have not been added to these effective power predictions. The effect of trim on resistance may be determined from comparison of the straightforward extrapolation of model experimental data, since wind drag and service margin corrections would merely be constant values added to all of the experimental data.

Table 4 assembles the effective horsepower predictions for all three trim conditions in the speed range from 18 to 22 knots. The predictions of effective power at the design speed of 21.5 knots have been plotted as a function of trim in Figure 2.

The resistance of the AO 177 hull at the design condition (1.5 foot (0.46 m) trim by the stern) repeated results of earlier experiments.¹ The resistance

¹References are listed on page 4 .

of the hull with the large bow-down trim of 3.5 feet (1.1 m) increased by approximately one and one half percent at the 21.5 knot design speed. The resistance of the hull with 1.0 foot (0.3 m) trim by the bow is only one-half percent higher than the resistance at the design condition. The small change in resistance is shown in Figures 1 and 2. From the data presented in these figures and in the tables it may be concluded that the effects of the bow-down trim on the resistance of the AO 177 hull are small.

The accuracy of the experimental measurements is approximately plus or minus one and one half percent, so the differences shown in these results are less than or equal to the inaccuracy of measurement. Nevertheless, the experiments showed a consistent trend of increasing resistance with increasing trim by the bow. This trend is considered valid.

REFERENCES

1. Hendrican, A. and K. Remmers, "Powering and Cavitation Performance for a Naval Fleet Oiler, AO 177 Class (Model 5326 with Propeller 4677)," DTNSRDC Ship Performance Department Report 544-14 (Jan 1976).




FIGURE 1 - Effective Powering Predictions for AO 177 represented by Model 5326, at Design Displacement and three trimmed conditions

$V_s = 21.5$ KNOTS
 $\Delta_s = 27390$ TONS




Figure 2 - Effective Power Requirement for AO 177 at 21.5 Knts in Various Trim Conditions

TABLE 1 - EFFECTIVE POWERING PREDICTIONS FOR AO 177 REPRESENTED BY MODEL 5326,
DESIGN DISPLACEMENT, TRIMMED 1.5 FT (0.46m) BY THE STERN

SHIP				MODEL			
LENGTH				21.93 FT (6.654 M)			
WETTED SURFACE				95.82 SQ FT (8.90 SQ M)			
DISPLACEMENT				1.57 TONS (1.60 T)			
LINEAR RATIO				25.682			
ITTC FRICTION LINE				.00050			
CORRELATION ALLOWANCE (CA)				.00050			
VS		PE		FRICTIONAL POWER		FN	V-L 10000
KNOTS	W/S	HP	KW	H	KW		
10.00	5.14	1460.9	1089.4	1149.2	856.9	.126	.422
12.00	5.17	2490.2	1857.0	1951.5	1455.2	.151	.567
14.00	7.20	3909.9	2915.6	3054.4	2277.6	.176	.567
16.00	8.23	5751.0	4288.5	4503.2	3358.1	.201	.554
18.00	9.26	8119.6	6054.8	6343.0	4730.0	.226	.554
19.00	9.77	9539.2	7113.4	7423.4	5535.6	.239	.561
20.00	10.29	11728.2	8745.7	8618.2	6424.6	.251	.707
20.50	10.55	13220.5	9858.5	9260.3	6905.4	.258	.836
21.00	10.80	15030.3	11208.1	9933.0	7407.0	.264	.887
21.50	11.06	17140.0	12781.3	10637.0	7932.0	.270	1.001
22.00	11.32	19629.5	14635.9	11373.1	8480.9	.276	1.190
23.00	11.83	25688.7	19156.1	12944.0	9652.4	.289	1.410
24.00	12.35	30940.8	23072.5	14651.3	10925.5	.302	1.905
							2.143

TABLE 2 - EFFECTIVE POWERING PREDICTIONS FOR AO 177 REPRESENTED BY MODEL 5326,
DESIGN DISPLACEMENT, TRIMMED 3.5 FT (1.07m) BY THE BOW

S-17P				MODEL			
LENGTH	560.64 FT (170.9 M)			21.83 FT (6.654 M)			
WETTED SURFACE	63021.50 FT (5855.50 M)			95.55 SQ FT (8.88 SQ M)			
DISPLACEMENT	27385.70 TONS (27825.7 T)			1.57 TONS (1.60 T)			
LINEAR RATIO				25.632			
ITTC FRICTION LINE							
CORRELATION ALLOWANCE (CA)				.00050			
VS		PE		FRICTIONAL POWER		FN	
KNOTS	M/S	HP	KW	H	KW	HP	100002
10.00	5.14	1455.8	1085.3	1145.9	854.5	.126	.567
12.00	6.17	2483.2	1851.7	1945.0	1451.1	.151	.567
14.00	7.20	3907.8	2914.1	3045.7	2271.2	.176	.573
16.00	8.23	5813.3	4335.0	4490.5	3349.6	.201	.589
18.00	9.26	8275.7	6171.2	6325.1	4716.6	.226	.610
19.00	9.77	9674.0	7213.9	7402.4	5520.0	.239	.604
20.00	10.29	11853.0	8838.8	8593.9	6408.4	.251	.743
20.50	10.55	13291.7	9911.6	9234.1	6885.9	.254	.859
21.00	10.80	15241.7	11365.7	9904.9	7384.1	.264	1.051
21.50	11.06	17374.9	12856.4	10605.9	7909.6	.270	1.242
22.00	11.32	19805.5	14769.7	11340.9	8456.9	.276	1.450
23.00	11.83	26063.0	19435.2	12907.4	9625.1	.289	1.972
24.00	12.35	31580.9	23549.9	14609.9	10894.6	.302	2.239

TABLE 4

COMPARISON OF EFFECTIVE POWER PREDICTIONS FOR AO 177
 REPRESENTED BY MODEL 5326, DESIGN DISPLACEMENT, FULLY
 APPENDED, AT THREE TRIMMED CONDITIONS: 1.5 X FT X STERN,
 3.5 FT X BOW, AND 1.0 FT X BOW

V-KNOTS	EXP 1	EXP 2	EXP 3
	P_{E-h_p}	P_{E-h_p}	P_{E-h_p}
	1.5 FT X STERN	3.5 FT X BOW	1.0 FT X BOW
18.0	8120	8276	8206
20.0	11728	11853	11686
20.5	13221	13292	13163
21.0	15030	15242	15101
21.5	17140	17375	17222
22.0	19629	19807	19628

DTNSRDC ISSUES THREE TYPES OF REPORTS

1. DTNSRDC REPORTS, A FORMAL SERIES, CONTAIN INFORMATION OF PERMANENT TECHNICAL VALUE. THEY CARRY A CONSECUTIVE NUMERICAL IDENTIFICATION REGARDLESS OF THEIR CLASSIFICATION OR THE ORIGINATING DEPARTMENT.

2. DEPARTMENTAL REPORTS, A SEMIFORMAL SERIES, CONTAIN INFORMATION OF A PRELIMINARY, TEMPORARY, OR PROPRIETARY NATURE OR OF LIMITED INTEREST OR SIGNIFICANCE. THEY CARRY A DEPARTMENTAL ALPHANUMERICAL IDENTIFICATION.

3. TECHNICAL MEMORANDA, AN INFORMAL SERIES, CONTAIN TECHNICAL DOCUMENTATION OF LIMITED USE AND INTEREST. THEY ARE PRIMARILY WORKING PAPERS INTENDED FOR INTERNAL USE. THEY CARRY AN IDENTIFYING NUMBER WHICH INDICATES THEIR TYPE AND THE NUMERICAL CODE OF THE ORIGINATING DEPARTMENT. ANY DISTRIBUTION OUTSIDE DTNSRDC MUST BE APPROVED BY THE HEAD OF THE ORIGINATING DEPARTMENT ON A CASE-BY-CASE BASIS.

END

DATE
FILMED

7-81

DTIC